View finder for 8K Camera and Camcorder High-Definition View Finder

DF-3516/DF-3516-A



Features

- Supports Multi-formats
 Supports multiple video format such as 60i, 24sF, 50i etc.
- High-definition/High-response OLED panel
 High response OLED panel with full HD resolution (1920×1080)
- Focus function

Camera focusing functions such as magnification, marker, peaking, etc.

- Waveform display function
 Display the video luminance waveform
- HDR video display function
 Display the video with high brightness HDR
 - * DF-3516-A has changed the layout of the dedicated composite cable connection terminals upward.

Specification

Display Method

Item	Specifications
Display Type	OLED
Display Color	8-bit
Contrast Aspect	10000: 1 and more
Brightness	120cd/m ²
Resolution	1920 (H) × 1080 (V) Pixels
Frame Rate	60Hz, 50Hz, 48Hz

Input Signal Specification

Item	Specifications
HD-SDI Input	SMPTE ST 292-1 Compliant
	Field frequency:
	Automatic tracking such as 60.00/59.94[Hz] and automatic tracking of input format.
3G-SDI Input	SMPTE ST 425-1 Compliant
	Field frequency:
	Automatic tracking such as $60.00/59.94[Hz]$ and automatic tracking of input format.

General Specification

Item	Specifications
Power Requirement	DC10-17V
Power Consumption	7W(typ)
Operating Temperature Range	0 to 40°C
Operating Humidity Range	20 to 80%RH (No Condensation)
Dimensions	76.2 (W) × 78 (H) × 135 (D) mm (Excluding Protrusions)
Weight	0.5kg



 Contact to:
 * The specifications are subjected to change without notice.

 TOKYO Headquarters
 1-5-2 Minami-yukigaya, Ota-ku, Tokyo, Japan 145-006
 TEL +81-(0)3-5734-6320
 FAX +81-(0)3-5734-6102

 USA OFFICE
 780 Montague Expressway, Suite 302, San Jose CA 95131 USA
 TEL +1-408-435-7800
 FAX +1-408-435-7900

 URL http://www.astro-americas.com
 DF3516.3516-A-4607E-1
 DF3516.3516-A-4607E-1